

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
24 July 2003 (24.07.2003)

PCT

(10) International Publication Number
WO 03/060498 A1

(51) International Patent Classification⁷: G01N 23/20,
23/207

(21) International Application Number: PCT/EP03/00546

(22) International Filing Date: 21 January 2003 (21.01.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
MI02A000097 21 January 2002 (21.01.2002) IT

(71) Applicant and

(72) Inventor: BERTI, Giovanni [IT/IT]; Via Piero di Puccio,
3, I-56126 Pisa (IT).

(74) Agent: GERVASI, Gemma; Notarbartolo & Gervasi
S.P.A., Corso di Porta Vittoria, 9, I-20122 Milan (IT).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE,
SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,
VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI,
SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: DIFFRACTOMETER AND METHOD FOR DIFFRACTION ANALYSIS



(57) Abstract: Diffractometer and method for diffraction analysis making use of two Euler cradles, a primary and a secondary Euler cradle. The primary Euler cradle supports a source of a radiation beam, having a collimation axis, and a radiation beam detector, having a reception axis, said collimation and reception axis, conveying in a centre of the diffractometer which is fixed with respect to the primary Euler cradle. The source and detector are adapted to move along the primary Euler cradle. The secondary Euler cradle supports the primary Euler cradle and is arranged to rotate the latter.